

SunTherm Line Card

MS Series

High Efficiency Multi-Position Electric Air Handler



- High Efficiency Constant Torque Motor
- High Efficiency Variable Speed ECM Motor
- Upflow or Horizontal Application
- DX or Chilled Water Cooling
- Heat Pump, Electric or Hot Water Heating
- 208/240V-1ph-60Hz (Electric Heat Models)
- DX A2L RDS and TXV installed for R-32 and R-454B




MS Series

High Efficiency Multi-Position Hydronic Air Handler



- High Efficiency Constant Torque Motor
- High Efficiency Variable Speed ECM Motor
- Upflow or Horizontal Application
- DX or Chilled Water Cooling
- Heat Pump, Electric or Hot Water Heating
- Hydronic Control Board with 6 Hour Pump timer to meet water circulation requirement in certain states
- 115V-1ph-60Hz (Hot Water Heat Models)
- DX A2L RDS and TXV installed for R-32 and R-454B



MMVE Series

High Efficiency Multi-Position Hydronic Air Handler



- High Efficiency Variable Speed ECM Motor
- Multi-Position Ready
- Ease of Installation
- Full Insulated Cabinet and Door
- Reversible Front Panel for Downflow Applications
- Side Return Option



SunTherm Line Card

MMVT Series

Multi-Position Modular Air Handler



- Available in the following cabinet sizes:
 - a. 14 ½” wide x 28” Deep
 - b. 17 ½” wide X 28” Deep
 - C. 21” Wide X 28” Deep
 - D. 24 ½” Wide X 28” Deep
- Multi-Position Ready
- Ease of Installation
- High Efficiency Blower
- Full Insulated Cabinet and Door
- Reversible Front Panel for Downflow Applications
- Side Return Option



S-Series and High Efficiency HE Series

Cased Ceiling Mounted Fan Coil



- Uncased Unit
- DX or Chilled Water Cooling
- Electric, Hot Water or Heat Pump Heating
- 208/240V-1ph-60Hz (Electric Heat Models)
- 115V-1ph-60Hz (Hot Water Heat Models)
- Compact Concealed Design
- Easy Access For Service and Maintenance
- Add-On Electric Heat up to 10kw
- DX A2L RDS and TXV installed for R-32 and R-454B



C-Series and High Efficiency HE Series

Cased Ceiling Mounted Fan Coil



- DX or Chilled Water Cooling
- Electric, Hot Water or Heat Pump Heating
 - 208/240V-1ph-60Hz (Electric Heat Models)
 - 115V-1ph-60Hz (Hot Water Heat Models)
 - Compact Concealed Design
 - Easy Access For Service and Maintenance
 - Add-On Electric Heat up to 10kw
 - DX A2L RDS and TXV installed for R-32 and R-454B



B/S-02/03 Series

Wall Mount Air Handlers with Electric Heating



Standard Features:

- Recessed "In the Wall" or Closet Mounted
- Prewired for Cooling and Heating Operation
- Heavy Gauge Embossed Galvanized Steel Cabinet
- 208/240V-1ph-60Hz (Electric Heat Models)
- Slide-Out Blower for Easy Maintenance
- DX A2L RDS and TXV installed for R-32 and R-454B
- Chilled water Cooling Available



B/S/H-02/03 Series

Wall Mount Air Handlers with Hot Water Heating



Standard Features:

- Recessed "In the Wall" or Closet Mounted
- Prewired for Cooling and Heating Operation
- Heavy Gauge Embossed Galvanized Steel Cabinet
- 115V-1ph-60Hz (Hot Water Heat Models)
- Hot Water Heat Models Include Circulating Pump and Check Valve
- Includes Hydronic Control Board with built in 6 Hour Pump to meet water circulation requirement in some states.
- Slide-Out Blower for Easy Maintenance
- DX A2L RDS and TXV installed for R-32 and R-454B
- Chilled water Cooling Available



AHW1 - 2 Series

Wall Mount Air Handlers (Electric and Hydronic)



- Recessed "In the Wall" or Closet Mounted
 - Add-on Up To 10kW Electric Heat
 - Up To 3 Tons Of Cooling
 - Optional Louvered/Solid Door Available
 - 208/240V-1ph-60Hz (Electric Heat Models)
 - 115V/ 1PH/ 60HZ (Hot Water Models)
- DX A2L RDS and TXV installed for R-32 and R-454B



Printed in U.S.A © Copyright 2026 SunTherm 2PG ST10P0326

Mortex Products Inc. 501 Terminal Road Fort Worth, Texas 76106 800.444.6354 www.mortx.com